

SROBOTIQ

PPLICATS +



CER

ACCORD AND

PLUG + PLAY COMPONENTS



SOFTWARE

APPLICATION KIT



SURFACE FINISHING KIT



INSIGHTS



Robot not included

APPLICATION SOLUTIONS

PALLETIZING SOLUTION

The Robotiq Palletizing Solution redefines ease of use for automated palletizing platforms. Create your program in minutes—directly on the teach pendant—to automatically generate all robot movements and trajectories. Elevate your workforce with easy-to-use robot solutions that do the work for you.



SCREWDRIVING SOLUTION

The Robotiq Screwdriving Solution gets the work done right in simple small-screw assemblies.

Thanks to the 5-minute changeovers it enables, manufacturers can produce multiple products per assembly line.

MACHINE TENDING SOLUTION

Getting robots up and running is complex and can leave you feeling overwhelmed. With the Machine Tending Solution, we deliver peace of mind that your machines will always be running with accessible automation.

Increase your machine's capacity and reduce downtime with an easy-to-use Robotiq solution that does the work for you.





WHO WE ARE

Manufacturers struggle to put robots to work in their factories because it's still too costly and too complicated. Robotiq's tools and know-how simplify collaborative robot applications, so factories can start production faster. Robotiq works with a global network of connected robot experts supporting their local manufacturers.

OUR MISSION

Free human hands from repetitive tasks

AT A GLANCE

12,000+ Hands Freed




300+ Channel partners globally



LEAN ROBOTICS

Save time with a **step-by-step methodology** that helps you go from a manual task to a robotic one.








amazon.com


RESOURCES



Empower yourself with Robotiq products and cobot applications, using the only elearning platform integrating Lean Robotics concepts.

elearning.robotiq.com







📿 Case Studies

There's nothing like real life examples to see the difference Robotiq Plug + Play Components make. Watch how companies, big and small, are deploying robots in their factories and how they improved their business with Robotig.


robotiq.com/resource-center/case-studies



We love writing about different aspects of robotics and automation. In fact, we've written dozens of eBooks, all available for **free** in our resource center.

robotiq.com/resource-center/ebooks







Get technical insights from cobot experts

DoF is where industrial automation professionals share their know-how and get answers. Working together, DoF Pros accelerate their robotics projects.

dof.robotiq.com

Ready to automate?

Blueprints is a **free service** that helps manufacturers accelerate their robotic cell process.

1. Access **blueprints.robotiq.com** to describe and document your current task.

2. Our integration coaches will help you automate it.





THE ROBOT

- > Factory proven hardware
- > The most user-friendly software for cobots
- > Product synergy between each component
- > 10 years of experience in cobot applications
- > 99% satisfaction rate in proof-of-concept and support services

DFFERENCE




ROBOTIQ

A PPLICATION Solutions

PALLETIZING SOLUTION

Automation should simplify your life. Not make it more complicated.









IT'S ALL CONNECTED

No need to design or program the connection between the robot controller and hardware; we've done it.

All the elements included in the box are connected, so you don't have to spend any time on this.

HIGH PERFORMANCE

Earn an ROI faster than with other cobot solutions, because of the high performance cycle time.

What makes it perform so well? The Robotiq software generates optimized cobot motions based on the pallet layout. It also synchronizes motion control of the cobot and 7th axis for the AX Series. Plus, seamless movements mean a longer life cycle for your cobot.

FITS EASILY WITHIN YOUR EXISTING FLOOR PLAN

The Robotiq Palletizing Solution fits easily within your existing floor plan, given its small footprint. No need to reorganize your floor layout around a central robot.

SAFETY FIRST


Because safety is crucial, we've built an environment for safe integration. We also support third-party safeguard devices.



AX Series fully integrated vertical axis



PE Series manually adjustable pedestal



PE Series teach pendant stand and operator box




WHAT'S THE DIFFERENCE?



SET UP YOUR APPLICATION **IN 3 EASY STEPS**

All you need to do is create the pallet pattern to automatically generate and optimize all trajectories and robot movements.





3 SET PALLET PATTERN





CONFIGURATOR

Still not sure our solution is for you? Easily validate product fit for your application.

Plus, find out whether the AX Series or PE Series is a better fit for you.

All you need:

- 1. Box dimensions, weight and orientation
- 2. Pallet dimensions
- 3. Pallet pattern

Validate KPIs and solution fit right from the start with your own data!



SPECIFICATIONS

| Box | AX Series | PE Series |
|-----------------------|--------------------|-----------------------|
| Max payload with EOAT | Up to Up to | 16 kg 35 lb |
| Max box throughput | Up 13 cycle | o to es/min* |
| Min box dimensions | 50 x 50 x 2 x 2 | |

*Depending on box weight, dimensions, and surface, as well as pallet dimensions and layout.

| Pallet | AX Series | PE Series |
|---------------------------|--|-----------|
| Pallet dimensions – width | from 300 to 1219 mm from 12 to 48 in. | |
| Pallet dimensions – depth | from 300 to 1219 mm from 12 to 48 in. | |
| Pallet height (empty) | min 50 mm min 2 in. | |
| Pallet height (filled) | max 2750 mm max 108 in. | |
| Number of box patterns | Two max | |

ROBOTIQ PALLETIZING SOLUTION

SKUs

| SOL-PAL-UR-1500 | ROBOTIQ PALLETIZING SOL AX-SERIES | ROBOTIC PALLETIZING SOLUTION AX-SERIES *NO GRIPPER INCLUDED IN THIS SKU* 1 x 7th axis base including: 1 x Mechanically welded assembly 1 x Vertical axis 1500mm 1 x Motor 1 x Control Motion Box (PLC, Drive, safety relay) 4 x Pallet sensors 2 x Beacon Lights for status 1 x Cable management system 1 x Box detection sensor 1 x Material Handling Copilot software dongle license Used for robots: UR10 CB-Series and e-Series |
|---------------------|--|---|
| SOL-PAL-UR-PDSTL | ROBOTIQ PALLETIZING SOL PE-SERIES | ROBOTIQ PALLETIZING SOLUTION PEDESTAL PE-SERIES *NO GRIPPER INCLUDED IN THIS SKU* 1 x pedestal base including: 1 x Mechanically welded assembly 1 x Control Box (PLC) 4 x Pallet sensors 2 x Status Lights with 10m cable 1 x Teach pendant holder with operator buttons 1 x Cable management system 1 x Box detection sensor 1 x Material Handling Copilot software dongle license Used for robots: UR10, UR10e and UR16e |
| SOL-PAL-UR-VAC-1500 | ROBOTIQ PALLETIZING SOL 1.5 M / AIRPICK | ROBOTIC PALLETIZING SOLUTION 1.5 M WITH AIRPICK VACUUM GRIPPER 1 x 7th axis base including: 1 x Mechanically welded assembly 1 x Vertical axis 1500mm 1 x Motor 1 x Control Motion Box (PLC, Drive, safety relay) 4 x Pallet sensors 2 x Beacon Lights for status 1 x Cable management system 1 x Box detection sensor 1 x Extra reach bracket 1 x Vacuum Gripper kit (Airpick, suctions cups, brackets for 2 or 4 cups) 1 x Air tube 8mm 1 x Gripper coupling kit 1 x Material Handling Copilot software dongle license |

SKUs

ROBOTIQ PALLETIZING SOLUTION

| SOL-PAL-UR-VAC-PDSTL | ROBOTIQ PALLETIZING SOL PDSTL / AIRPICK | ROBOTIC PALLETIZING SOLUTION PEDESTAL WITH AIRPICK VACUUM GRIPPER 1 x Declestal base including: 1 x Mechanically welded assembly 1 x Control Box (PLC) 4 x Pallet sensors 2 x Status Lights with 10m cable 1 x Teach pendant holder with operator buttons 1 x Cable management system 1 x Box detection sensor 1 x Scather areach bracket 1 x Vacuum Gripper kit (Airpick, suctions cups, brackets for 2 or 4 cups) 1 x Gripper coupling kit 1 x Material Handling Copilot software dongle license |
|-----------------------|--|---|
| DEMO | | |
| PAL-UR-VAC-1500-DEMO | DEMO ROBOTIQ PALLETIZING SOLUTION 1.5M | DEMO OF ROBOTIO PALLETIZING SOLUTION 1.5 M WITH AIRPICK VACUUM GRIPPER AX-SERIES 1 x 7th axis base including: 1 x Mechanically welded assembly 1 x Vertical axis 1500mm 1 x Motor 1 x Control Motion Box (PLC, Drive, safety relay) 4 x Pallet sensors 2 x Beacon Lights for status 1 x Cable management system 1 x Box detection sensor 1 x Extra reach bracket 1 x Vacuum Gripper kit (Airpick, suctions cups, brackets for 2 or 4 cups) 1 x Gripper coupling kit 1 x Material Handling Copilot software dongle license |
| PAL-UR-VAC-PDSTL-DEMO | DEMO ROBOTIQ PALLETIZING SOLUTION PDSTL | DEMO OF ROBOTIO PALLETIZING SOLUTION PEDESTAL WITH AIRPICK VACUUM GRIPPER PE-SERIES 1 x pedestal base including: 1 x Mechanically welded assembly 1 x Control Box (PLC) 4 x Pallet sensors 2 x Status Lights with 10m cable 1 x Teach pendant holder with operator buttons 1 x Cable management system 1 x Box detection sensor 1 x Extra reach bracket 1 x Vacuum Gripper kit (Airpick, suctions cups, brackets for 2 or 4 cups) 1 x Material Handling Copilot software dongle license Used for robots: UR10, UR10e and UR16e |

ROBOTIQ SCREWDRIVING SOLUTION

Elevate your workforce

- Consistent screwdriving around the clock.
- 5-min production changeovers.
- Complete solution designed for flexible automation of your screwdriving tasks.





Fewer injuries and a happier workforce

When you automate a screwdriving task, you keep employees from harm and can redirect them to value-added tasks. Elevate your workforce with a simple and easy-to-use automation solution.

CONSISTENT SCREWDRIVING AROUND THE CLOCK

- Free workers for higher-value tasks
- Reduce repetitive strain injuries
- Improve product quality
- Solve labor shortages







A single fastening solution to handle production changeovers **in small-screw assembly**

Deploy and master your robotic screwdriving application by adding Robotiq Screwdriving Solution to a UR cobot. So intuitive, no robotics experience is required.

Get a simple, cost-effective automation solution, and say hello to consistent screwdriving around the clock.

Designed for **flexible automation**

- Buy "off the shelf"
- Automate easily, without massive investment
- Intuitive to deploy and duplicate
- 5-min production changeovers

Screwdriving Fit Tool https://links.robotiq.com/screwdrivingfittool

PROGRAM YOUR APPLICATION IN 2 EASY STEPS

| 1 PICK SCREW COMMAND | 2 DRIVE SCREW COMMAND |
|---|---|
| Command Graphics Variables | Command Graphics Variables |
| Pick Screw | Drive Screw |
| Select the digital inputs of the Screw Feeder. Feeder status digital_in[1] • • • Screw ready digital_in[0] • • Screw ready digital_in[0] • • Signty insert the screwdriving bit in the screw drive and tap on Set pick position. Set pick position Move to pick pos The approach position is preset with a 10 mm offset. Move to approach Tap the Test button to cycle through the Pick Screw program. Test | Stop condition Torque (metr Tool speed 500 RPM Force applied on screw 10.0 N Image: Teach Test Advanced settings: Angle before ramp down 0 deg Left-Hand Threads Error Conditions Retry on failure Distance tolerance (±) 5.0 mm Image: Timeout |

Control the screwdriver

directly from the UR Toolbar to use, test or set it.

Seamlessly integrate

the force sensing, vacuum, cobot, screwdriver, and screw feeder.

Automatically apply error-proofing functions to improve productivity and quality.



ROBOTIQ SCREWDRIVING SOLUTION

SPECIFICATIONS

| Screwdriver SD-100 | Min | Typical | Max |
|--------------------|--|-------------------|-------------------------|
| Torque range | 0.5 Nm 4.5 in-lb | - | 4 Nm 35 in-lb |
| Torque precision | - | ±10% ¹ | - |
| Screw diameter | M2.5 #3 | - | M5 #10 |
| Speed | 1 RPM | - | 500 RPM |
| Air consumption | - | 65 L/min | - |
| Weight | 1.5 kg <i>3.3 lb</i> | | |
| Dimensions | 272 mm x 143.5 mm x 75 mm <i>10 3/4 x 5 5/8 x 3 in</i> | | |
| Warranty | 2M cycles or 1 year under normal operation | | |
| ESD-safe | Yes | | |

1. Value at initial factory calibration. Torque precision typically increases when calibrated in operating conditions, depending on joint materials.

| Screw Feeder SF-300 | Min | Мах |
|------------------------|---|-----------------|
| Screw diameter | M2.5 #3 | M5 #10 |
| Screw length | 6 mm ¹ 1/4 in | 25 mm 1 in |
| Screw head height | - | 5 mm 3/16 in |
| Typical feed rate | - | 3 s per screw |
| Screw chamber volume | 300 сс | |
| Dimensions (W x D x H) | 157 mm x 286 mm x 171 mm 6 3/16 x 11 ¼ x 6 3/4 in | |
| Power supply | 120/220V AC to 24V DC | |
| Weight | 5.2 kg 11.4 lb | |
| Warranty | 2M cycles or 1 year under normal operation | |
| ESD-safe | Yes | |

1. For socket head screws, the minimum screw length is 10mm. Please validate with your Robotiq representative for shorter screws.

ROBOTIQ SCREWDRIVING SOLUTION

OVERVIEW

| Feature | What is it? | Advantage |
|---|--|---|
| Error-proofing | Pre-programmed error-detection and recovery functions:Screw presence detection.Torque and screw position control.OK/Not OK confirmation. | Ensures correct torque is applied. Prevents screw transport failures. Prevents fastening failures. Saves programming time. |
| Vacuum transportation system | Integrated vacuum system that allows for reliable screw transport while ensuring maximal slender reach. | Allows the robot to validate screw presence at all times. Allows the system to transport screws of any material. Requires no customization. Enables maximal reach into tight spaces. |
| One-SKU solution | With one SKU, you get the screwdriver, screw feeder, screwdriver bits and vacuum sleeves, screwdriving URCap, and the latest force-sensing technology. | Simplifies ordering.Simplifies tracking. |
| Dual sensors in screw feeder | Dual sensor indicates both screw ready and screw cleared from workspace. | Prevent pick command from activating if a screw is not ready. Avoid collisions. Coordinate robot and screw feeder movements. |
| Automated communication between every components | Getting separate components (screw feeder, screwdriver, robot, and more) to communicate has never been easier. | Simple programming to help you master your processes.Decrease deployment time. |
| Designed to reach tight spaces | We've designed a compact and lightweight screwdriver with flexible vacuum sleeves for optimum screwdriving. | Allows screwdriving in chamber holes.Allows screwdriving in tight spaces. |
| Open program tree | Robotiq Screwdriving URCap integrates the force sensing and force control functions to automatically program a pick and a screw, but the program tree is open for you to develop any advanced programming sequence. | • Adapt the solution to fit your unique application. |

SERVICES

At Robotiq, we strive to free more human hands from repetitive tasks. To do so, we offer tools and services to empower you to deploy your project on your own and master your processes.

SCREWDRIVING PROOF OF CONCEPT

Our team of coaches is here to help you prove that our solution can work for your application, as well as avoid technical issues and simplify your introduction to the robot world.

Examples services:

- Demonstrate application fit
- Validate cycle time
- Demonstrate repeatability

REMOTE AND ONSITE TRAININGS FOR ROBOTIQ SCREWDRIVING SOLUTION

Our training aims to fast-track your introduction to the ever-growing collaborative robot industry.

- Intro to cobots
- Solution installation
- Solution operation
- Troubleshooting and maintenance
- Calibration
- Force Copilot for Assembly





SKUs

ROBOTIQ SCREWDRIVING SOLUTION

| SOL-SDS-CB-D1F3-IH | Screwdriving Sol. CB-Series Imp. Hex | Robotiq Screwdriving Solution for CB-Series Robots with Imperial Hex Socket Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit FT 300-S Force Torque Sensor Kit Imperial Hex Socket Screwdriving Bit Starting Kit (5/64, 7/64, 3/32 in.) |
|--------------------|--------------------------------------|--|
| SOL-SDS-CB-D1F3-MH | Screwdriving Sol. CB-Series Met. Hex | Robotiq Screwdriving Solution for CB-Series Robots with Metric Hex Socket Screwdriving Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit FT 300-S Force Torque Sensor Kit Metric Hex Socket Screwdriving Bit Starting Kit (2, 2.5, 3 mm) |
| SOL-SDS-CB-D1F3-P | Screwdriving Sol. CB-Series Phillips | Robotiq Screwdriving Solution for CB-Series Robots with Phillips Screwdriving Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit FT 300-S Force Torque Sensor Kit Phillips Screwdriving Bit Starting Kit (PH1 & PH2) |
| SOL-SDS-CB-D1F3-T | Screwdriving Sol. CB-Series Torx® | Robotiq Screwdriving Solution for CB-Series Robots with Torx[®] Screwdriving Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit FT 300-S Force Torque Sensor Kit Torx[®] Screwdriving Bit Starting Kit (T8, T10, T15, T20) |
| SOL-SDS-ES-D1F3-IH | Screwdriving Sol. e-Series Imp. Hex | Robotiq Screwdriving Solution for e-Series Robots with Imperial Hex Socket Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit Force Copilot Software Imperial Hex Socket Screwdriving Bit Sarting Kit (5/64, 7/64, 3/32 in.) |
| SOL-SDS-ES-D1F3-MH | Screwdriving Sol. e-Series Metric HS | Robotiq Screwdriving Solution for e-Series Robots with Metric Hex Socket Screwdriving Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit Force Copilot Metric Hex Socket Screwdriving Bit Starting Kit (2, 2.5, 3 mm) |

ROBOTIQ SCREWDRIVING SOLUTION

SKUs

| SOL-SDS-ES-D1F3-P | Screwdriving Sol. e-Series Phillips | Robotiq Screwdriving Solution for e-Series Robots with Phillips Screwdriving Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit Force Copilot Software Phillips Screwdriving Bit Starting Kit (PH1 & PH2) |
|-------------------|-------------------------------------|--|
| SOL-SDS-ES-D1F3-T | Screwdriving Sol. e-Series Torx® | Robotiq Screwdriving Solution for e-Series Robots with Torx[®] Screwdriving Bit Starting Kit Complete Solution that Includes: SD-100 Screwdriver Basic Kit SF-300 Screw Feeder Basic Kit Force Copilot Software Torx[®] Screwdriving Bit Starting Kit (T8, T10, T15, T20) |
| SOL-SDS-SD100 | SD-100 Screwdriver Basic Kit | SD-100 Screwdriver Basic Kit Including: SD-100 Screwdriver Cables, Hose and Mechanical Coupling Complete Vacuum Sleeve Kit Note: Force Copilot Software (NOT included in this kit) is required to operate No Screw Feeder Included (See our Complete Screwdriving Solutions) No Screwdriver Bit Included No Vacuum Regulator Included |
| SOL-SDS-SF300 | SF-300 Screw Feeder Basic Kit | SF-300 Screw Feeder Basic Kit Including: SF-300 Screw Feeder Power Supply, Cables and Fixing Brakets Note: No Screwdriver Included (See Our Complete Screwdriving Solutions) |

ROBOTIQ SCREWDRIVING SOLUTION

DEMO

MACHINE TENDING SOLUTION

Automation should simplify your life. Not make it more complicated.



Keep chips flying

Getting robots up and running is complex and can leave you feeling overwhelmed. With the Machine Tending Solution, we deliver peace of mind that your machines will always keep running through accessible automation.





Increase your machine's capacity and reduce downtime


with an easy to use Robotiq solution that does the work for you.

Create programs 75% faster than with traditional programming, thanks to guidance on setting key waypoints and simple action menus.




SET KEY WAYPOINTS

Once they're set, they become reference points for your operations.



2 REFINE OPERATIONS

Use our action menus and adapt the solution to your needs.



3 CREATE YOUR SMART MOVES


Machine Tending Copilot creates optimized movements between your key waypoints, finding the best path through the pre-defined flyzone and automatically avoiding collisions within the workcell.



IT COULDN'T BE EASIER!

Instead of hard-wiring the machine like with traditional automation, our communication modules are non-invasive and do not require installation by certified technicians

The solution can be deployed in 2–3 hours.



| | Single gripper | Double gripper |
|-------------------|--|--|
| System core | Machine Tending Copilot software Robotiq MT controller Pneumatic panel Button Activator Air nozzle kit | |
| Gripper | Hand-E adaptive gripper MT fingertips starting kit | 2x Hand-E adaptive grippers 2x MT fingertips starting kit Dual bracket + New compact dual Hand-E bracket |
| Machine interface | Stacklight detector Footswitch activator (if lathe) | |
| Add-ons | Robotiq Wrist Camera Robotiq adjustable pedestal | |



Press buttons on the HMI



Monitor machine status



Control workholding

Robotiq Wrist Camera (Optional)



Ideal for faster blank programming and picking parts in an unstructured environment.

- CAD file import teaching (.dxf)
- Automatic part teaching (user defined arbitrary shape)
- Parametric part teaching (circle, ring, square, rectangle)
- Edge editing, object color and clearance validation
- Automatic and manual camera parameters: exposure, focus, LED lighting, white balance

SKUs

ROBOTIQ MACHINE TENDING SOLUTION

| SOL-MT-ES-DUAL-HND | Machine Tending Solution-Dual Hand-E | 1 x Machine Tending Copilot for UR E-Series 1 x Button Activator 1 x Air Nozzle Kit 2 x Machine Tending Fingertips starting kit 1 x Robotiq Machine Tending Controller 1 x Pneumatic Panel 1 x Dual Hand-E Gripper kit 1 x Compact dual Hand-E bracket 1 x Installation Hardware 1 x Quick Start Guide |
|----------------------|--|---|
| SOL-MT-ES-SINGLE-HND | Machine Tending Solution-Single Hand-E | 1 x Machine Tending Copilot for UR E-Series 1 x Button Activator 1 x Air Nozzle Kit 1 x Machine Tending Fingertips starting kit 1 x Robotiq Machine Tending Controller 1 x Pneumatic Panel 1 x Hand-E Gripper 1 x Installation Hardware 1 x Quick Start Guide |

MACHINE INTERFACE

| SOL-MT-FOOT-ACT | Footswitch activator | 1 x Footswitch Actuator 1 x 5m Pneumatic Tubing 1 x Pneumatic Valve kit 1 x Installation Hardware Requires a kit of the MACHINE TENDING SOLUTION family |
|-----------------|----------------------|--|
| SOL-MT-STK-LGHT | Stack light detector | 3 x Photo Sensors 3 x 2.5m Extension Cable 1 x Installation Hardware Requires a kit of the MACHINE TENDING SOLUTION family |

ADD-ONS

ROBOTIQ MACHINE TENDING SOLUTION

| RWC5-UR-KIT | Wrist Camera Kit for UR | 1 x Robotiq Wrist Camera unit 1 x Universal Robot pattern tool plate 1 x USB Stick 1 x USB Software Licence Dongle 1 x 4 ports USB hub 1 x Calibration Board 1 x Colored background 1 x Wrist Camera Tags (5) |
|--|---|--|
| SOL-MT-BUT-ACT-KIT | Button activator kit | 1 x Button Activator 1 x 5m Pneumatic Tubing 1 x Pneumatic Components Note: This kit is intended as a 2nd button activator when required |
| SOL-ROBOT-ADJ-PED | Robotiq adjustable pedestal | 1 x Adjustable Pedestal 1 x Installation Hardware Compatible with UR5, UR5e, UR10, UR10e, UR16e |
| SOL-ROBOT-CBL-MNGT-UR5 SOL-ROBOT-CBL-MNGT-UR10 SOL-ROBOT-CBL-MNGT-UR16 | Cable management sleeve kit for universal robots | 2 x Flexible Wrap-Around Robotic Cable Management. Compatible with UR5, UR5e, UR10, UR10e, UR16e |

DEMO

| SOL-MT-DEMO-KIT Machine Tending Solution Demo Kit | 1 x Demo Copilot for UR E-Series 1 x Button Activator 1 x Footswitch Activator 1 x Air Nozzle Kit 1 x Stack Light Detector 2 x Machine Tending Fingertips starter kit 1 x Robotiq Machine Tending Controller 1 x Pneumatic Panel 1 x Compact Dual Hand-E Bracket 1 x Dual Adapter Plate 1 x M8 Splitter Dual Coupling UR e-Series |
|---|---|
|---|---|

PLUG + PLAY COMPONENTS





THE GRIPPER FOR COLLABORATIVE ROBOTS

- Plug + Play and easy to program
- Ideal for precision assembly tasks
- Ergonomic shape for hand-guiding
- Built for industrial applications and harsh environments
- Automatic part detection, position feedback, and part validation









Quality Testing

SPECIFICATIONS

| Stroke (adjustable) | 50 mm | 2 in |
|---------------------------------|----------------|-----------------|
| Grip force (adjustable) | 20 to 185 N | 4.5 to 41 lbf |
| Form-fit grip payload | 5 kg | 11 lbs |
| Friction grip payload* | 4,7 kg | 8.8 lbs |
| Gripper weight | 1 kg | 2 lbs |
| Position resolution (fingertip) | 0.4 mm | |
| Closing speed (adjustable) | 20 to 150 mm/s | 0.8 to 5.9 in/s |
| Communication protocol | Modbus RT | U (RS-485) |
| Ingress protection (IP) rating | IP6 | 57 |

* Calculated for the use of silicon covered fingertips to grip a steel object, at a low robot acceleration.

** All specifications provided for reference only. See user manual at support.robotiq.com for official specifications.



SKUs

| HND-ES-UR-KIT | Hand-E Gripper Kit for UR e-Series | 1 x Hand-E Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Hand-E Fingertip Starting Kit 1 x End-Effector Coupling Kit for e-Series (UR) |
|---------------|------------------------------------|---|
| HND-GRP | Hand-E Basic Gripper Unit | 1 x Hand-E Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x screw kit |
| HND-UR-KIT | Hand-E Gripper Kit for UR | 1 x Hand-E Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Hand-E Fingertip Starting Kit 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
| HND-UR-KIT-W | Hand-E Wrist Connect Kit for UR CB | 1 x Hand-E Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Hand-E Fingertip Starting Kit 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x Micro-USB to USB cable |

DEMO

| HND-DEMO-KITHand-E Gripper Demo Kit for UR1 x Hand-E Basic Gripper Unit 1 x Hand-E Fingertip Starting Kit 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter 1 x End-Effector Coupling Kit for UR e-Series 1 x I/O Coupling Kit for CB series | HND-DEMO-KIT |
|---|--------------|
|---|--------------|



COMBOS

| CUR-DUAL-HND | Two (2) Hand-E Gripper Combo for UR | 2 x Hand-E Basic Gripper Unit (with flat rubber overmolded fingertips) 2 x Hand-E Fingertip starter kit 2 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter 1 x Dual Adapter Plate 1 x M12 Splitter male to 2 female |
|------------------------|--|---|
| CUR-ES-DUAL-HND | Combo of Two Hand-e for UR e-series | 2 x Hand-E Basic Gripper Unit (with flat rubber overmolded fingertips) 2 x Hand-E Fingertip starter kit 2 x End-Effector Coupling Kit for e-Series 1 x Dual Adapter Plate 1 x M8 Splitter - Dual Coupling UR e-Series |
| CUR-HND-RWC5 | Hand-E & Wrist Camera Combo for UR | 1 x Hand-E Gripper Basic Unit (with flat rubber overmolded fingertips) 1 x Hand-E Fingertip Starting Kit 1 x Wrist Camera kit for UR |
| CUR-HND-RWC5- FTS-S | Hand-E, Camera and FT300-S Combo for UR | 1 x Hand-E Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |
| CUR-READY | Hand-E Eserie force copilot insight | 1 x Hand-E Basic Gripper Unit 1 x Hand-E Fingertip Starting Kit 1 x Gripper Coupling Kit for e-Series (UR) 1 x Screw kit 1 x Force Copilot dongle key 1 x Yearly subscription to Insights (to be sent by email) Used for robots: Eserie cobot from Universal Robot |
| HND-FTS-S-UR-KIT | Hand-E and FT 300 Sensor Kit for UR | 1 x Hand-E Gripper Kit for UR CB 1 x FT300 S Sensor kit for UR |

2F ADAPTATIVE GRIPPERS



5 kg

0.9 kg

0.4 mm

20 to 150 mm/s

IP40

Modbus RTU (RS-485), RS-485, RS-232

* All specifications provided for reference only. See user manual at support.robotiq.com for official specifications.

Friction grip payload

Position resolution (fingertip)

Closing speed (adjustable)

Communication protocol

Ingress protection (IP) rating

Gripper weight

2.5 kg

1 kg

0.6 mm

30 to 250 mm/s

IP40

2F ADAPTATIVE GRIPPERS

| AGC-ES-UR-KIT-140 | 2F-140 Gripper Kit for UR e-Series | 1 x 2F-140 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x End-Effector Coupling Kit for e-Series |
|-------------------|------------------------------------|--|
| AGC-ES-UR-KIT-85 | 2F-85 Gripper Kit for UR e-Series | 1 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x End-Effector Coupling Kit for e-Series |
| AGC-GRP-2F140 | 2F-140 Basic Gripper Unit | 1 x 2F-140 Basic Gripper Unit 1 x Parallel mechanism locking pins 1 x Screw kit |
| AGC-GRP-2F85 | 2F-85 Basic Gripper Unit | 1 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Parallel mechanism locking pins 1 x Screw kit |
| AGC-UR-KIT-002 | 2F-85 Gripper kit for UR | 1 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
| AGC-UR-KIT-140 | 2F-140 Gripper kit for UR | 1 x 2F-140 Basic Gripper Unit 1 x End Effector Coupling for Bolt Pattern ISO 9409-1-50-4-M6 (with 1 m Pigtail Cable) 1 x 10 m Robotiq Device Cable 1 x USB to RS485 Adapter 1 x Parallel mechanism locking pins 1 x Screw Kit for Fixing End Effector Coupling on UR Robots |
| AGC-UR-KIT-140-W | 2F-140 Wrist Connect Kit for UR CB | 1 x Gripper 2F-140 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x Nicro-USB to USB cable |
| AGC-UR-KIT-85-W | 2F-85 Wrist Connect Kit for UR CB | 1 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x Micro-USB to USB cable |

DEMO

SKUs

| AGC-DEMO-KIT-002 | 2F-85 demo kit for Distributors | 1 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x End-Effector Coupling Kit 1 x End-Effector Coupling Kit for UR e-Series 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter 1 x I/O Coupling Kit for UR CB series 1 x 2F-85 Gripper collaborative protector kit |
|------------------|---------------------------------|--|
|------------------|---------------------------------|--|

2F ADAPTATIVE GRIPPERS

COMBOS

| AGC-FTS-S-UR-KIT-002 | 2F-85 Gripper and FT 300-S Sensor UR kit | 1 x Gripper 2F-85 UR CB Kit 1 x FT300-S Sensor kit for UR 1 x 4 ports USB hub |
|------------------------|---|---|
| AGC-FTS-S-UR-KIT-140 | 2F140 & FT 300-S Sensor kit for UR | 1 x 2F-140 Gripper UR CB Kit 1 x FT300-S Sensor kit for UR 1 x 4 ports USB hub |
| CUR-AGC-085-RWC5 | Combo of 2F85 and Wrist Camera for UR | 1 x 2F-85 Gripper Basic Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR |
| CUR-AGC-085-RWC5-FTS-S | Combo of 2F85, Camera & FT300-S for UR | 1 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |
| CUR-AGC-140-RWC5 | Combo of 2F140 and Wrist Camera for UR | 1 x 2F-140 Gripper Basic Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR |
| CUR-AGC-140-RWC5-FTS-S | Combo of 2F140, Camera & FT300-S for UR | 1 x 2F-140 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |
| CUR-DUAL-AGC-085 | Combo of Two 2F-85 for Universal Robots | 2 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 2 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter 1 x Dual Adapter Plate 1 x M12 Splitter male to 2 female |
| CUR-DUAL-AGC-140 | Combo of Two 2F-140 for Universal Robots | 2 x 2F-140 Basic Gripper Unit (with flat rubber overmolded fingertips) 2 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter 1 x Dual Adapter Plate 1 x M12 Splitter male to 2 female |
| CUR-ES-DUAL-AGC-085 | Combo of Two 2F-85 for UR e-series | 2 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 2 x End-Effector Coupling Kit for e-Series 1 x Dual Adapter Plate 1 x M8 Splitter - Dual Coupling UR e-Series |
| CUR-ES-DUAL-AGC-140 | Combo of Two 2F-140 for UR e-series | 2 x 2F-140 Basic Gripper Unit (with flat rubber overmolded fingertips) 2 x End-Effector Coupling Kit for e-Series 1 x Dual Adapter Plate 1 x M8 Splitter - Dual Coupling UR e-Series |

3-FINGER ROBOT GRIPPERS





PROVEN DESIGN

- Rugged and reliable
- Fully metallic
- High payload

TAKE FULL CONTROL

Adjust the gripper's position, speed, and force until it grasps your object perfectly

EXTREMELY WIDE STROKE

Open up to 155 mm with the encompassing grip mode









Quality Testing

SPECIFICATIONS

| Stroke (programmable) | 155 mm |
|--|---|
| Grip force (programmable) | 30 to 70 N |
| Form-fit grip payload | 10 kg |
| Friction grip payload | 2.5 kg |
| Finger position repeatability (fingertip grip) | 0.05 mm |
| Closing speed (programmable) | 22 to 110 mm/s |
| Gripper weight | 2.3 kg |
| Primary communication protocol | Modbus RTU (RS-485) |
| Secondary communication protocol options | Modbus TCP, EtherNet/IP, PROFINET, EtherCAT, DeviceNet, CANopen |

* All specifications are provided for reference only. See User Manual at support.robotiq.com for official specifications.



AGS-UR-KIT 3-Finger Adaptive Gripper kit for UR • 1 x 3-Finger Adaptive Gripper with Modbus TCP option • 1 x 10 m high flex Supply Cable • 1 x 10m Communication Cable • 1 x USB Cable • 1 x Grease syringe • 1 x 3-Finger Coupling S-101 • 1 x 3-Finger Wrist Adapter Plate S-157 • 1 x 3-Finger Wrist Adapter Plate S-157

DEMO

| AGS-DEMO-KIT Demo kit for distributors (3F) | 1 x 3-Finger Adaptive Gripper with Modbus TCP option 1 x Power supply 24V/2.7A 1 x 3-Finger demo kit carrying case |
|---|--|
|---|--|

СОМВО

| AGS-FTS-S-UR-KIT 3F Gripper a | nd FT300-S Sensor kit for UR | 1 x 3F Gripper UR KIT 1 x FTS300 Sensor kit for UR |
|-------------------------------|------------------------------|---|
|-------------------------------|------------------------------|---|



SMOOTH HANDLING FOR YOUR APPLICATIONS



SPECIFICATIONS

| | EPick | Air Pick |
|-------------------------------|-----------------------|-----------------------|
| Energy source | Electricity | Compressed air |
| Gripper weight | 710 g | 481 g |
| Maximum Vacuum level | 80% | 85% |
| Maximum Vacuum flow | 12 L/min | 52,7 L/min |
| Air consumption | - | 135,9 L/min |
| Minimum Feed pressure | - | 3 bar |
| Maximum Feed pressure | - | 7 bar |
| Connection, compressed air | - | 8 mm OD Tube |
| Operating ambient temperature | 5 to 40 °C | 0 to 50 °C |
| Humidity | 20-80% non condensing | 20-80% non condensing |

FULLY CUSTOMIZABLE EASY TO INTEGRATE EASY TO USE


UP AND RUNNING IN 30 MINUTES



- Powerful vacuum flow
- Low noise
- Compact design for cobots



- No air supply
- Perfect for non porous material
- Easy to handle



Mounts directly on Robotiq products and standard coupling for Robotiq products

High quality vacuum generator

Compact manifold to connect the suction cup system

Bracket and unique air nodes allowing full customization

Standard G1/4 thread suction cups





| VAC-CB-UR-AIRPICK-KIT1 | AirPick Kit for CB-Series UR / 1 Cup | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Tubing 8mm - 8m 1 x Vacuum cup (1.5 bellows, 55 mm diameter) 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
|--------------------------|---|--|
| VAC-CB-UR-AIRPICK-KIT1-W | AirPick Wrist Connect Kit UR CB / 1 cup | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x I/O Coupling 1 x Micro-USB to USB cable 1 x Vacuum cup (1.5 bellows, 55 mm diameter) 1 x Tubing 8mm - 8m |
| VAC-CB-UR-AIRPICK-KIT2 | AirPick Kit for CB-Series UR / 2 Cups | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 2 Suction Cups System - two (2) cups (with two (2) of each: vacuum cups of 40mm and 55mm) 1 x Tubing 8mm - 8m 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
| VAC-CB-UR-AIRPICK-KIT2-W | AirPick Wrist Connect Kit UR CB / 2 cups | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x Micro-USB to USB cable 1 x Kit 2 Suction Cups System - two (2) cups (with two (2) of each: vacuum cups of 40mm and 55mm) 1 x Tubing 8mm - 8m |
| VAC-CB-UR-AIRPICK-KIT4 | AirPick Kit for CB-Series UR / 4 Cups | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 4 Suction Cups System- four (4) cups (with four (4) of each: vacuum cups of 40mm and 55mm) 1 x Tubing 8mm - 8m 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
| VAC-CB-UR-AIRPICK-KIT4-W | AirPick Wrist Connect Kit UR CB / 4 cups | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x I/O Coupling 1 x Micro-USB to USB cable 1 x Kit 4 Suction Cups System- four (4) cups (with four (4) of each: vacuum cups of 40mm and 55mm) 1 x Tubing 8mm - 8m |
| VAC-ES-UR-AIRPICK-KIT1 | AirPick Kit for e-Series UR / 1 Cup | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Tubing 8mm - 8m 1 x Vacuum cup (1.5 bellows, 55 mm diameter) 1 x End-Effector Coupling Kit for e-Series (no protector) |



| VAC-ES-UR-AIRPICK-KIT2 | AirPick Kit for e-Series UR / 2 Cups | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 2 Suction Cups System - two (2) cups (with two (2) of each: vacuum cups of 40mm and 55mm) 1 x Tubing 8mm - 8m 1 x End-Effector Coupling Kit for e-Series (no protector) |
|------------------------|---|--|
| VAC-ES-UR-AIRPICK-KIT4 | AirPick Kit for e-Series UR / 4 Cups | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 4 Suction Cups System- four (4) cups (with four (4) of each: vacuum cups of 40mm and 55mm) 1 x Tubing 8mm - 8m 1 x End-Effector Coupling Kit for e-Series (no protector) |
| VAC-GRP-AIRPICK | AIRPICK Basic Gripper Unit | 1 x Pneumatic vacuum generator 1 x Screw kit 1 x Vacuum cup (1.5 bellows, 40 mm diameter) |

DEMO

| VAC-UR-KIT-AIRPICK-DEMO | AirPick Demo Kit for Partners on UR | 1 x Pneumatic vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 4 Suction Cups System- four (4) cups (with four (4) of each: vacuum cups of 40mm and 55mm) 1 x Vacuum Suction Cup plate for two (2) cups 1 x Tubing 8mm - 8m 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter 1 x End-Effector Coupling Kit for e-Series (no protector) 1 x I/O Coupling Kit for CB series |
|-------------------------|--|---|
|-------------------------|--|---|



| VAC-CB-UR-EPICK-KIT1 | EPick Kit for CB-Series for UR / 1 cup | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Vacuum cup (1.5 bellows, 55 mm diameter) 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
|------------------------|--|---|
| VAC-CB-UR-EPICK-KIT1-W | EPick Wrist Connect Kit UR CB / 1 cup | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x I/O Coupling 1 x Micro-USB to USB cable 1 x Vacuum cup (1.5 bellows, 55 mm diameter) |
| VAC-CB-UR-EPICK-KIT2 | EPick Kit for CB-Series for UR / 2 cups | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 2 Suction Cups System - two (2) cups (with two (2) of each: vacuum cups of 40mm and 55mm) 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
| VAC-CB-UR-EPICK-KIT2-W | EPick Wrist Connect Kit UR CB /2 cups | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x Micro-USB to USB cable 1 x Kit 2 Suction Cups System - two (2) cups (with two (2) of each: vacuum cups of 40mm and 55mm) |
| VAC-CB-UR-EPICK-KIT4 | EPick Kit for UR CB-Series/ 4 cups | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 4 Suction Cups System- four (4) cups (with four (4) of each: vacuum cups of 40mm and 55mm) 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter |
| VAC-CB-UR-EPICK-KIT4-W | EPick Wrist Connect Kit UR CB / 4 cups | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x I/O Coupling Kit including: 1 x I/O Coupling 1 x Micro-USB to USB cable 1 x Suction system for four (4) cups |
| VAC-ES-UR-EPICK-KIT1 | EPick Kit for e-Series for UR / 1 cup | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Vacuum cup (1.5 bellows, 55 mm diameter) 1 x End-Effector Coupling Kit for e-Series |
| VAC-ES-UR-EPICK-KIT2 | EPick Kit for e-Series for UR / 2 cups | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 2 Suction Cups System - two (2) cups (with two (2) of each: vacuum cups of 40mm and 55mm) 1 x End-Effector Coupling Kit for e-Series |



| VAC-ES-UR-EPICK-KIT4 | EPick Kit for UR e-Series / 4 cups | 1 x Electrical vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 4 Suction Cups System- four (4) cups (with four (4) of each: vacuum cups of 40mm and 55mm) 1 x End-Effector Coupling Kit for e-Series |
|----------------------|---------------------------------------|---|
| VAC-GRP-EPICK | EPICK Basic Gripper Unit | 1 x Electrical vacuum generator 1 x Screw kit 1 x Vacuum cup (1.5 bellows, 40 mm diameter) |

DEMO

| VAC-UR-KIT-EPICK-DEMO EPick Demo Kit - UR (E and CB Series) | 1 x Electric vacuum generator (with one (1) vacuum cup 1.5 bellows, 40 mm diameter) 1 x Kit 4 Suction Cups System- four (4) cups (with four (4) of each: vacuum cups of 40mm and 55mm) 1 x Vacuum Suction Cup plate for two (2) cups 1 x End-Effector Coupling Kit 1 x 10 m Robotiq device cable 1 x USB to RS485 adapter 1 x End-Effector Coupling Kit for e-Series (UR) 1 x I/O Coupling Kit for CB series |
|--|---|
|--|---|

сомво

| | CUR-READY-VACUUM EPick 1cup Force Copilot Insights 1year Used | 1 x Electrical vacuum generator 1 x End effector coupling kit for e-Series 1 x Vacuum cup (1.5 bellows, 55 mm diameter) 1 x Quickstart guide 1 x Force Copilot dongle key 1 x Yearly subscription to Insights (to be sent by email) 1 x Lean Robotiq book d for robots: e-Series cobot from Universal Robot |
|--|--|---|
|--|--|---|





THE PIONEER OF **COBOT FORCE TORQUE SENSORS**

- Plug + Play for quick and easy integration •
- Fully metallic hardware suited for industrial needs •
- Wear-free sensing technology means no calibration • needed, no production downtime
- High resolution and no loss of precision over time •
- Force Copilot programming software included .











SPECIFICATIONS

| | FX | FY | FZ | MX | MY | MZ |
|---|-----------------------------------|---------|------|---------|----------|----------|
| Measuring range | | ± 300 N | | ± 30 Nm | | |
| Overload capacity | | 500% | | 500% | | |
| Signal noise | | 0.1 N | | 0.005 | ō Nm | 0.003 Nm |
| Recommended threshold for contact detection | | 1 N | | 0.02 | Nm | 0.01 Nm |
| Tool deflection at maximum measurable load | 0.01 mm | | 0.17 | deg | 0.09 deg | |
| External noise sensitivity | Immune | | | | | |
| Data output rate (data stream mode) | 100 Hz | | | | | |
| Weight | 440 g | | | | | |
| Communication protocol | Modbus RTU / Data stream (RS-485) | | | | | |
| IP Rating | IP65 | | | | | |

* All specifications are provided for reference only. See User Manual at support.robotiq.com for official specifications.



| FTS-300-S-KIT-001 | FT 300-S Sensor Standard Kit | 1 x FT 300-S sensor without mechanical coupling 1 x Power and communication cable 1 x RS-485 to USB converter |
|-------------------|------------------------------|---|
| FTS-300-S-SEN-001 | FT-300 S Basic Sensor Unit | 1 x FT 300 S sensor alone (no coupling, no cables) 1 x Screw kit |
| FTS-300-S-UR-KIT | FT 300-S Sensor kit for UR | 1 x FT 300-S Basic Sensor Unit 1 x Mechanical coupling for UR 1 x 10m High-Flex Cable 1 x USB to RS485 Adapter |

DEMO

| FTS-300-S-DEMO-KIT | FT 300-S Demo kit | 1 x FT 300-S Basic Sensor Unit 1 x Mechanical coupling for UR 1 x 10m High-Flex Cable 1 x USB to RS485 Adapter |
|--------------------|-------------------|---|
|--------------------|-------------------|---|

COMBOS

| AGC-FTS-S-UR-KIT-002 | 2F-85 Gripper and FT 300-S Sensor UR kit | 1 x Gripper 2F-85 UR CB Kit 1 x FT300-S Sensor kit for UR 1 x 4 ports USB hub |
|------------------------|--|--|
| AGC-FTS-S-UR-KIT-140 | 2F140 & FT 300-S Sensor kit for UR | 1 x 2F-140 Gripper UR CB Kit 1 x FT300-S Sensor kit for UR 1 x 4 ports USB hub |
| AGS-FTS-S-UR-KIT | 3F Gripper and FT300-S Sensor kit for UR | 1 x 3F Gripper UR KIT 1 x FTS300 Sensor kit for UR |
| CUR-AGC-085-RWC5-FTS-S | Combo of 2F85, Camera & FT300-S for UR | 1 x 2F-85 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |
| CUR-AGC-140-RWC5-FTS-S | Combo of 2F140, Camera & FT300-S for UR | 1 x 2F-140 Basic Gripper Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |
| HND-FTS-S-UR-KIT | Hand-E and FT 300 Sensor Kit for UR | 1 x Hand-E Gripper Kit for UR CB 1 x FT300 S Sensor kit for UR |



EASY TO USE

- Teach, edit, and run via the teach pendant
- Accelerate changeovers with Visual Offset
- Operate with any expertise level

CAD IMPORT

DXF

VISUAL OFFSET

CODE READING













FAST & REPEATABLE PART DETECTION



| APPLICATIONS | | |
|--------------------------|-----------------------|---|
| FE/ | ATURES | BENEFITS |
| CAD |) Import | Teach a model using your own CAD file |
| One- | -click workplane | Create additional workplanes for your pick and place application with only one click |
| PICK & PLACE | o-pick | Automatically creates the picking action with a centered position |
| | metric part teaching | Ideal for faster blank programming |
| Grip | per clearance check | Robust program minimizes production downtime |
| Visua MACHINE TENDING | al offset | Use the Robotiq tag to offset the robot program and accelerate changeovers |
| Imag | • | Perform real time quality control Trace parts in a product assembly Program picture parameters for a personalized visual traceability |
| | oe programming wizard | Program complex parts in minutes Simultaneously manage different parts for flexible assembly sequences Enables robot to work in structured or unstructured environments |

SPECIFICATIONS

| Sensor & Optics | 5 MP color sensor, electrically adjustable focus, 70 mm to infinity |
|------------------------------|--|
| Integrated Lighting | Two units (diffused white LED) |
| Programmable Parameters | CAD file import teaching (.dxf) Automatic part teaching (user defined arbitrary shape) Parametric part teaching (circle, ring, square, rectangle) Edge editing, object color and clearance validation Automatic and manual camera parameters: exposure, focus, LED lighting, white balance |
| Electrical | Direct communication with UR controller (via USB), and power supply from controller (24 V) |
| Weight | 160 g |
| Operating Temperature | 0°C to 50°C |
| Camera Internal Image Buffer | DRAM memory |

* All specifications are provided for reference only. See User Manual at support.robotiq.com for official specifications.



| RWC5-CAM-001 | Replacement Wrist Camera | 1 x Robotiq Wrist Camera with 5m High Flex cable 1x Screw kit |
|--------------|--------------------------|---|
| RWC5-UR-KIT | Wrist Camera Kit for UR | 1 x Robotiq Wrist Camera unit 1 x Universal Robot pattern tool plate 1x USB stick 1 x USB Software Licence Dongle 1 x 4 ports USB hub 1 x Calibration Board 1 x Colored background 1 x Wrist Camera Tags (5) |

DEMO

| RWC5-DEMO-KIT | Wrist Camera Demo Kit for UR | 1 x Robotiq Wrist Camera unit 1 x Universal Robot pattern tool plate 1 x USB Software Licence Dongle 1 x 4 ports USB hub 1 x Calibration Board 1 x Colored background 1 x Wrist Camera Tags (5) |
|---------------|------------------------------|---|
|---------------|------------------------------|---|

COMBOS

| CUR-AGC-085-RWC5 | Combo of 2F85 and Wrist Camera for UR | 1 x 2F-85 Gripper Basic Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR |
|------------------|--|--|
| CUR-AGC-085- | Combo of 2F85, Camera & FT300-S | 1 x 2F-85 Basic Gripper Unit |
| RWC5-FTS-S | for UR | (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |
| CUR-AGC-140-RWC5 | Combo of 2F140 and Wrist Camera for UR | 1 x 2F-140 Gripper Basic Unit (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR |
| CUR-AGC-140- | Combo of 2F140, Camera & FT300-S | 1 x 2F-140 Basic Gripper Unit |
| RWC5-FTS-S | for UR | (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |
| CUR-HND-RWC5 | Hand-E & Wrist Camera Combo for UR | 1 x Hand-E Gripper Basic Unit (with flat rubber overmolded fingertips) 1 x Hand-E Fingertip Starting Kit 1 x Wrist Camera kit for UR |
| CUR-HND-RWC5- | Hand-E, Camera and FT300-S Combo | 1 x Hand-E Basic Gripper Unit |
| FTS-S | for UR | (with flat rubber overmolded fingertips) 1 x Wrist Camera kit for UR 1 x FT300-S Sensor kit for UR |

APPLICATION KITS

SANDING KIT



AUTOMATE ONE OF THE TOUGHEST, DIRTIEST JOBS

- Save hours of programming
- Increase quality and productivity
- Reduce worker injuries
- The only complete sanding solution for Universal Robots

WHAT'S INCLUDED

- Finishing Colilot
- Orbital tool
- Braket
- Sanding Media
- Quick Start Guide
- Air control Accessories



SUPPORTED MATERIALS






CARBON FIBER

GENERATE A FINISHING PATH IN MINUTE

Program complex finishing trajectories by teaching less than 10 waypoints, even on complex, spherical surfaces. Apply constant force at each cycle.





PRO TIPS

Robotiq is a pioneer in force control for collaborative robots. Our sanding **e-learning platform** includes our best lessons learned in the past 10 years. Use it to save hours of programming: elearning.robotiq.com.

VALIDATE PART LOCATION

The contact offset node uses reference points on the part to validate its position. If there's a slight change, the robot program automatically adapts all related parameters.



SPECIFICATIONS

| Random orbital sander | |
|-----------------------|---|
| Maximum air supply | 6.2 bar (90 PSI) |
| Air flow (full speed) | 450 L/min (16 SCFM) |
| Pad diameter | 5" |
| Media | Hook and loop; 5 holes |
| Orbit diameter | 3/16″ |
| Maximum speed | 12,000 RPM |
| Air supply inlet | 1/4" NPT thread |
| Dust exhaust | Central vacuum ready; 1" (25 mm) diameter. |

| Robotiq bracket | |
|-------------------------|--|
| Weight | 0.42 kg |
| Added height | 9 mm |
| Compatible sanders | Dynabrade 56854B, 56819B, 56830B, 56863B, 56844B, 57404B, 57814B |
| Control valve | |
| Air supply inlet/outlet | 1/4" NPT thread |
| Sanding media kit | |
| Grits | 60, 80, 120, 320, 400 |

SANDING KIT

SKUs

| SAND-ES-UR-KIT | Sanding Kit for UR e-Series | 1 x Air random orbital sander with Mounting kit onto UR robot 1 x Finishing Copilot kit for UR e-Series 1 x Air control accessories |
|----------------------|---|---|
| SAND-FTS-S-CB-UR-KIT | Sanding Kit & FT 300-S for UR CB-Series | 1 x Air random orbital sander with Mounting kit onto UR robot 1 x FT 300 S Sensor kit for UR 1 x Air control accessories. |

DEMO

| SAND-ES-UR-KIT-DEMO | Sanding Kit Demo for UR e-Series | 1 x Dynabrade sander and mounting 1 x Finishing Copilot software dongle license 1 x Air control accessories |
|---------------------|----------------------------------|---|
|---------------------|----------------------------------|---|

SURFACE FINISHING KIT



AUTOMATE ONE OF THE TOUGHEST, DIRTIEST JOBS

- Save hours of programming
- Increase quality and productivity
- Connect with the world's leading finishing tools

WHAT'S INCLUDED

- Finishing Copilot dongle license
- Mirka mechanical bracket
- Dynabrade mechanical bracket
- Valve accessories kit
- Robot program template



SUPPORTED MATERIALS




EASY TO INTEGRATE, EASY TO USE

Finishing applications for collaborative robots require many hardware and software components to communicate together. Integration can take months... but not anymore! The surface finishing kit is the only hardware and software all-in-one solution for cobots.

PROGRAM IN MINUTES

Teach a finishing path on a flat surface out of only 4 waypoints and let the program adjust to different part sizes. Add custom weaving movements specific to your process in no time.





GENERATE COMPLEX PATHS

Program complex finishing trajectories by teaching fewer than 10 waypoints. Finishing Copilot generates a complete path and applies consistent force at each cycle, whether it's on a curved (6 waypoints), or spherical (9 waypoints) surface.

VALIDATE PART LOCATION

The contact offset node uses reference points on the part to validate its position. If there's a slight change, the robot program automatically adapts all related parameters.



SPECIFICATIONS

| Pneumatic specifications | |
|----------------------------------|----------|
| Valve maximum operating pressure | 8.3 Bars |
| Valve input port | 1/4 NPT |
| Electrical Specifications | |
| Air supply inlet/outlet | 24 V |

| Mirka bracket | |
|--|-------------------------|
| External enveloppe without sander | [77 89 37] mm |
| Added height | 7 mm |
| Product weight without sander | 0.221 kg |
| | |
| Dynabrade bracket | |
| Dynabrade bracket External enveloppe without sander | [100 119 31] mm |
| | [100 119 31] mm 9 mm |

SURFACE FINISHING KIT

SKUs

| MIRKA-SCREW-KIT | Mirka screw kit | • Screw kit to fix Mirka sander on UR robot |
|----------------------|--|---|
| SAND-APL-ROS-002 | Mounting bracket kit for Mirka sander | 1 x Mechanical Bracket 1 x Mirka Screw Kit |
| SURF-ES-UR-KIT | Surface Finishing kit for UR e-Series | 1 x Finishing Copilot software dongle license 1 x Mounting kit for Dynabrade and Mirka Orbital Sanders 1 x Air control accessories ****Refer to User Manual for sanders compatibilities |
| SURF-FTS-S-CB-UR-KIT | Surface Finishing kit for UR CB-Series | Surface Finishing kit & FT 300-S for UR CB Series Included: 1 x FT 300 S Sensor kit for UR 1 x Mounting kit for Dynabrade and Mirka Orbital Sanders 1 x Air control accessories ****Refer to User Manual for sanders compatibilities |

SOFTWARE



INTUITIVE SOFTWARE FOR FT 300 AND E-SERIES ONBOARD FORCE TORQUE SENSOR









Separation Contraction















INDEX PARTS

ALIGN WITH HOLE



FINISHING C PILOT



A SOFTWARE MADE FOR FINISHING APPLICATIONS

- Save hours of programming
- Generate finishing trajectories in minutes
- Compensate for external tool wear
- Set an external tool center point
- Operate with any level of expertise

OTHER FEATURES

- Find a surface
- Perform various insertions
- Hand-guide your robot
- Follow complex trajectories
- Edit point-to-point trajectories
- Apply constant force and define the stiffness for each axis
- Reset sensor values to zero

AUTOMATE FINISHING TASKS THE EASY WAY





COMPENSATE FOR TOOL WEAR


The contact offset node uses a point on the external tool as a reference to measure wear. Contact offset validates the tool's exact position anytime you wish. If there's a slight change, the robot program automatically adapts all related parameters.

SET EXTERNAL TOOL CENTER POINT

Finishing Copilot lets you program an external TCP. This tells the robot that the finishing tool is external to the robot, unlike in most collaborative robot applications. The finishing task is then processed with the robot bringing the part to the external TCP.







VALIDATE PART POSITION

The contact offset node uses reference points on the part to validate its position. If there's a slight change, the robot program automatically adapts all related parameters.


GENERATE A FINISHING PATH IN MINUTES

Program complex finishing trajectories by teaching fewer than 10 waypoints. Whether it's on a flat (4 waypoints), curved (6 waypoints), or spherical (9 waypoints) surface, Finishing Copilot generates a complete path and applies consistent force at each cycle.



MACHINE TENDING C€PILOT

A SOFTWARE MADE FOR MACHINE TENDING Compatible with only UR+ end of arm tooling



Locate your tray between cycles to ensure repeatable part picking.



Validate your vise's exact position at any moment with a simple contact. The robot will automatically adapt all relevant parameters.



Move your robot from a machine to another without having to reprogram it.



Find the exact surface on your fixture to execute repeatable part positionning.

OTHER FEATURES

- Hand-guide your robot
- Follow complex trajectories
- Edit point-to-point trajectories
- Apply constant force and define the stiffness for each axis
- Reset sensor values to zero




FORCE COPILOT

SKUs

| CP-FORCE-ES-UR-KIT | Force Copilot kit for UR e-Series | 1 x Force Copilot License Dongle 1 x Teach Pendant Stylus 1 x UR Wrist Axis Sticker |
|--------------------|-----------------------------------|---|
| | | |

DEMO

| CP-FORCE-ES-UR-DEMO-KIT | Copilot Demo kit for UR e-Series | 1 x Full Copilot Software Suites License Dongle 1 x Teach Pendant Stylus 1 x UR Wrist axis sticker |
|-------------------------|----------------------------------|--|
| | | |



SKUs MACHINE TENDING C PILOT CP-MT-ES-UR-KIT Machine Tending Copilot for UR E-Series • 1 × Machine Tending Copilot License Dongle • 1 × Teach Pendant Stylus • 1 × UR Wrist Axis Sticker



REMOTE ACCESS

- Manage your robot from anywhere
- Get support from robotics expert


MONITOR PRODUCTION

- Get a real-time robot overview
- Define and track KPIs
- Receive daily reports

OPTIMIZE PERFORMANCE

- Track progress
- Analyze trends
- Download events log

HOW IT WORKS



3. Pair your robot with your **Insights Cloud Service** account.

Manage your robot from anywhere on insights.robotiq.com

INSIGHTS REQUIRES

UR3, UR5 or UR10 (with CB3.1 controller) • Internet connection .

PURCHASE OPTIONS

| | Insights License ¹ | Insights Starter Kit |
|--|-------------------------------|----------------------|
| Real-Time Robot Overview | \checkmark | \checkmark |
| Email Reports Scheduler | ✓ | \checkmark |
| Robot SMS Alerts | ✓ | \checkmark |
| Production Performance Timeline & KPIs | \checkmark | \checkmark |
| Robot Digital I/Os | \checkmark | \checkmark |
| Downloadable Events Log | ✓ | \checkmark |
| Remote Access | \checkmark | \checkmark |
| Backup and Robot Log Files | \checkmark | \checkmark |
| Preconfigured 4G LTE/Wi-Fi Router & antennas | | ✓ |
| Prepaid international SIM card ² | | \checkmark |
| Logitech C920 webcam | | ✓ |
| Connection cables & accessories | | \checkmark |

¹ 1-year term.

² Equivalent to a 1-month period.

Contact your local Robotiq distributor for pricing.

Subscription plans may change without prior notice.

INSIGHTS

SKUs

| INS-CXN-AME | Insights Connection Kit Americas | Preconfigured 4G LTE/ Wi-Fi Router & antennas (Americas) USA power supply & 24V power stripped cables Prepaid international SIM card Logitec C920 Camera Accessories: Ethernet cable, USB key, USB splitter, USB extension cable |
|-------------------|--|---|
| INS-CXN-EUR | Insights Connection Kit Europe & Asia | Preconfigured 4G LTE/ Wi-Fi Router & antennas (Europe & Asia) USA power supply & 24V power stripped cables Prepaid international SIM card Logitec C920 Camera Accessories: Ethernet cable, USB key, USB splitter, USB extension cable |
| INS-STK-AME-001 | Insights Starter Kit Americas | Insights 1-year advanced subscription plan: Remote Access Real-time dashboard Real-time robot alerts Performance reports Production Monitoring (KPI) Diagnostics Tools All software updates Insights connection kit Preconfigured 4G LTE/ Wi-Fi Router & antennas (Americas) USA power supply & 24V power stripped cables Prepaid international SIM card Logitec C920 Camera Accessories: Ethernet cable, USB key, USB splitter, USB extension cable |
| INS-STK-EUR-001 | Insights Starter Kit Europe & Asia | Insights Starter Kit Europe & Asia Included: Insights 1-year advanced subscription plan Remote Access Real-time dashboard Real-time robot alerts Performance reports Production Monitoring (KPI) Diagnostics Tools All software updates Note: Subscription plans may change without prior notice Insights connection kit Preconfigured 4G LTE/ Wi-Fi Router & antennas (Europe & Asia) USA power supply & 24V power stripped cables Prepaid international SIM card Logitec C920 Camera Accessories: Ethernet cable, USB key, USB splitter, USB extension cable |
| INS-SUB-ADV-001 | Insights One-Year Advanced Subscription | Real-time robot overview Email reports scheduler Robot SMS alerts Robot Remote Access Production performance timeline & KPIs Robot Digital I/Os Downloadable Events Log All software updates |
| INS-SUB-RENEW-001 | Insights Renewal / Monthly Adjustment | Remote Access Real-time dashboard Real-time robot alerts Performance reports Production Monitoring (KPI) Diagnostics tools All software updates Note: Subscription plans may change without prior notice |

INSIGHTS

DEMOS

| INS-STK-AME-DEMO | Insights Partner Demo kit - Americas | Insights unlimited partner subscription plan Remote Access Real-time dashboard Real-time robot alerts Performance reports Production Monitoring (KPI) Diagnostics Tools All software updates Note: Subscription plans may change without prior notice Insights connection kit Preconfigured 4G LTE/ Wi-Fi Router & antennas (Americas) USA power supply & 24V power stripped cables Prepaid international SIM card Logitec C920 Camera Accessories: Ethernet cable, USB key, USB splitter, USB extension cable |
|------------------|--|---|
| INS-STK-EUR-DEMO | Insights Partner Demo kit - Europe&Asia | Insights Partner Demo kit Europe & Asia Included: Insights unlimited partner subscription plan Remote Access Real-time dashboard Real-time robot alerts Performance reports Production Monitoring (KPI) Diagnostics Tools All software updates Note: Subscription plans may change without prior notice Insights connection kit Preconfigured 4G LTE/ Wi-Fi Router & antennas (Europe & Asia) USA power supply & 24V power stripped cables Prepaid international SIM card Logitec C920 Camera Accessories: Ethernet cable, USB key, USB splitter, USB extension cable |

START PRODUCTION FASTER

IN THE WORLD



CONTACT US AMERICAS

Sales

1-418-380-2788 ext. 2 iss@robotiq.com

Support

1-418-380-2788 ext. 3 support@robotiq.com

966, chemin Olivier, Suite 500, Lévis, QC, G7A 2N1, Canada

EUROPE

Lyon, France +33 4 81 13 27 10

13 avenue des Tulipiers 69500 Bron France

LET'S KEEP IN TOUCH

For any questions concerning robotic and automated handling or if you want to learn more about the advantages of using flexible electric handling tools, contact us.

Join us on social media:



OUR TEAM BEHIND THE PRODUCTS

We work hard, have fun and love what we do!

The team at Robotiq is what makes the products stand out.

We believe in what we do, and we're constantly seeking to **do more and better!**



